



Zoom in

## CEE-flanged plug 75x75 straight 32A 5p 6h IP67

CEE-flanged plug 75x75 straight 32A 5p 6h IP67

housing material: PA6

rated current: 32A

number of poles: 5 (3P+N+PE)

clock-position: 6h

rated voltage/frequency: 200/346V~ - 240/415V~ /  
50+60Hz

contacts: brass

connection technology: screw terminals

dimensions (flange/fixing center): 75x75 mm / 60x60  
mm

IP protection class: IP66/IP67



|                                    |                                                   |                               |                      |
|------------------------------------|---------------------------------------------------|-------------------------------|----------------------|
| Name                               | CEE-flanged plug 75x75<br>straight 32A 5p 6h IP67 | RAL-number                    |                      |
| IEC-amperage A                     | 32                                                | Degree of protection (IP)     | IP67                 |
| Voltage according to EN<br>60309-2 | 400 V (50+60 Hz) red                              | Connection system             | Screwed terminal     |
| Rated voltage V                    |                                                   | Construction type             | Built-up device plug |
| Rated frequency                    |                                                   | Angle of plug                 | Straight             |
| Number of poles                    | 5                                                 | Material                      | Plastic              |
| Clock hour position h              | 6                                                 | Contact material              | CuZn                 |
| Identification colour              | Red                                               | Surface treatment<br>contacts | Untreated            |