



Fuse-link, high speed, 5 A, AC 500 V, 50 kA, 14 x 51 mm, aR, UL



Part no. 500V 5Amp S/COND FERRULE 14.3 X 50.8MM
Catalog No. FWH-5A14F

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	5
Rated voltage			AC 500 V
Size			14 x 51 mm
Utilization category			aR
Breaking Capacity		kA	50
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical
Standards/Regulations			UL 248

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])			
Model			Ceramic fuse
Size			14x51 mm
Voltage type			AC/DC
Rated current		A	5
Rated voltage		V	500
Utilization category			aR (accompanied semiconductor protection)
Rated operating frequency		Hz	45 - 62
Type of fuse status indicator			Other
Release characteristic			Other
Breaking capacity		kA	50
Power loss at rated current		W	1.5