



**Contactor, 230 V 50/60 Hz, 4 pole, 380 V 400 V, 4 kW, Screw terminals, AC operation**



**Part no.** DILEM4(230V50/60HZ)  
**Catalog No.** 052506  
**Alternate Catalog No.** XTMF9A00G2


## Delivery program

|                                                           |                |    |                                                                                                                                                                                                                            |
|-----------------------------------------------------------|----------------|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product range                                             |                |    | Contactors                                                                                                                                                                                                                 |
| Application                                               |                |    | Mini Contactors for Motors and Resistive Loads                                                                                                                                                                             |
| Subrange                                                  |                |    | DILEM contactors                                                                                                                                                                                                           |
| Utilization category                                      |                |    | AC-1: Non-inductive or slightly inductive loads, resistance furnaces<br>NAC-3: Normal AC induction motors: starting, switch off during running<br>AC-4: Normal AC induction motors: starting, plugging, reversing, inching |
| Connection technique                                      |                |    | Screw terminals                                                                                                                                                                                                            |
| Number of poles                                           |                |    | 4 pole                                                                                                                                                                                                                     |
| <b>Rated operational current</b>                          |                |    |                                                                                                                                                                                                                            |
| AC-3                                                      |                |    |                                                                                                                                                                                                                            |
| 380 V 400 V                                               | $I_e$          | A  | 9                                                                                                                                                                                                                          |
| AC-1                                                      |                |    |                                                                                                                                                                                                                            |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                |    |                                                                                                                                                                                                                            |
| Open                                                      |                |    |                                                                                                                                                                                                                            |
| at 40 °C                                                  | $I_{th} = I_e$ | A  | 22                                                                                                                                                                                                                         |
| <b>Max. rating for three-phase motors, 50 - 60 Hz</b>     |                |    |                                                                                                                                                                                                                            |
| AC-3                                                      |                |    |                                                                                                                                                                                                                            |
| 220 V 230 V                                               | P              | kW | 2.2                                                                                                                                                                                                                        |
| 380 V 400 V                                               | P              | kW | 4                                                                                                                                                                                                                          |
| 660 V 690 V                                               | P              | kW | 4                                                                                                                                                                                                                          |
| AC-4                                                      |                |    |                                                                                                                                                                                                                            |
| 220 V 230 V                                               | P              | kW | 1.5                                                                                                                                                                                                                        |
| 380 V 400 V                                               | P              | kW | 3                                                                                                                                                                                                                          |
| 660 V 690 V                                               | P              | kW | 3                                                                                                                                                                                                                          |
| Contact sequence                                          |                |    |                                                                                                                                                                                                                            |
| For use with                                              |                |    | ...DILEM<br>...DILE                                                                                                                                                                                                        |
| Actuating voltage                                         |                |    | 230 V 50/60 Hz                                                                                                                                                                                                             |
| Voltage AC/DC                                             |                |    | AC operation                                                                                                                                                                                                               |

## Technical data

### General

|                                                |              |               |                                                                                |
|------------------------------------------------|--------------|---------------|--------------------------------------------------------------------------------|
| Standards                                      |              |               | IEC/EN 60947, VDE 0660, CSA, UL                                                |
| Lifespan, mechanical; Coil 50/60 Hz            | Operations   | $\times 10^6$ | 7                                                                              |
| Lifespan, mechanical                           | Operations   | $\times 10^6$ | 20                                                                             |
| Maximum operating frequency                    |              |               |                                                                                |
| Mechanical                                     |              | Ops./h        | 9000                                                                           |
| electrical (Contactors without overload relay) | Operations/h |               | Page 05/070                                                                    |
| Climatic proofing                              |              |               | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
| Ambient temperature                            |              |               |                                                                                |
| Open                                           |              | °C            | -25 - +50                                                                      |
| Enclosed                                       |              | °C            | - 25 - 40                                                                      |
| Storage                                        |              | °C            |                                                                                |

|                                                                       |                 |                                                                                    |
|-----------------------------------------------------------------------|-----------------|------------------------------------------------------------------------------------|
| Min. ambient temperature, storage                                     | °C              | - 40                                                                               |
| Ambient temperature, storage max.                                     | °C              | + 80                                                                               |
| Mounting position                                                     |                 | As required, except vertical with terminals A1/A2 at the bottom                    |
| Mounting position                                                     |                 |  |
| Mechanical shock resistance (IEC/EN 60068-2-27)                       |                 |                                                                                    |
| Half-sinusoidal shock, 10 ms                                          |                 |                                                                                    |
| Basic unit without auxiliary contact module                           |                 |                                                                                    |
| Main contacts, make contacts                                          | g               | 10                                                                                 |
| Basic unit with auxiliary contact module                              |                 |                                                                                    |
| Main contacts make contact                                            | g               |                                                                                    |
| Make                                                                  | g               | 10                                                                                 |
| Auxiliary contacts Make/break contacts                                | g               | 20 / 20                                                                            |
| Degree of Protection                                                  |                 | IP20                                                                               |
| Protection against direct contact when actuated from front (EN 50274) |                 | Finger and back-of-hand proof                                                      |
| Altitude                                                              | m               | Max. 2000                                                                          |
| Weight                                                                | kg              | 0.17                                                                               |
| Terminal capacity of auxiliary and main contacts                      |                 |                                                                                    |
| Screw terminals                                                       |                 |                                                                                    |
| Solid                                                                 | mm <sup>2</sup> | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5)                                               |
| Flexible with ferrule                                                 | mm <sup>2</sup> | 1 x (0.75 - 1.5)<br>2 x (0.75 - 1.5)                                               |
| Solid or stranded                                                     | AWG             | 18 - 14                                                                            |
| Stripping length                                                      | mm              | 8                                                                                  |
| Terminal screw                                                        |                 | M3.5                                                                               |
| Pozidriv screwdriver                                                  | Size            | 2                                                                                  |
| Standard screwdriver                                                  | mm              | 0.8 x 5.5<br>1 x 6                                                                 |
| Max. tightening torque                                                | Nm              | 1.2                                                                                |

### Main conducting paths

|                                         |                  |      |       |
|-----------------------------------------|------------------|------|-------|
| Rated impulse withstand voltage         | U <sub>imp</sub> | V AC | 6000  |
| Overvoltage category/pollution degree   |                  |      | III/3 |
| Rated insulation voltage                | U <sub>i</sub>   | V AC | 690   |
| Rated operational voltage               | U <sub>e</sub>   | V AC | 690   |
| Safe isolation to EN 61140              |                  |      |       |
| between coil and contacts               |                  | V AC | 300   |
| between the contacts                    |                  | V AC | 300   |
| Making capacity (cos φ to IEC/EN 60947) |                  | A    | 110   |
| Breaking capacity                       |                  |      |       |
| 220 V 230 V                             |                  | A    | 90    |
| 380 V 400 V                             |                  | A    | 90    |
| 500 V                                   |                  | A    | 64    |
| 660 V 690 V                             |                  | A    | 42    |
| Short-circuit protection maximum fuse   |                  |      |       |
| Type "2", 500 V                         | gL/gG            | A    | 10    |
| Type "1", 500 V                         | gL/gG            | A    | 20    |

### AC

|      |  |  |
|------|--|--|
| AC-1 |  |  |
|------|--|--|

|                                                           |                |     |                                                    |
|-----------------------------------------------------------|----------------|-----|----------------------------------------------------|
| Rated operational current                                 |                |     |                                                    |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz |                |     |                                                    |
| Open                                                      |                |     |                                                    |
| at 40 °C                                                  | $I_{th} = I_e$ | A   | 22                                                 |
| at 50 °C                                                  | $I_{th} = I_e$ | A   | 20                                                 |
| at 55 °C                                                  | $I_{th} = I_e$ | A   | 19                                                 |
| enclosed                                                  | $I_{th}$       | A   | 16                                                 |
| Notes                                                     |                |     | At maximum permissible ambient air temperature.    |
| Conventional free air thermal current, 1 pole             |                |     |                                                    |
| Notes                                                     |                |     | At maximum permissible ambient air temperature.    |
| open                                                      | $I_{th}$       | A   | 60                                                 |
| enclosed                                                  | $I_{th}$       | A   | 50                                                 |
| AC-3                                                      |                |     |                                                    |
| Rated operational current                                 |                |     |                                                    |
| Open, 3-pole: 50 – 60 Hz                                  |                |     |                                                    |
| Notes                                                     |                |     | At maximum permissible ambient temperature (open.) |
| 220 V 230 V                                               | $I_e$          | A   | 9                                                  |
| 240 V                                                     | $I_e$          | A   | 9                                                  |
| 380 V 400 V                                               | $I_e$          | A   | 9                                                  |
| 415 V                                                     | $I_e$          | A   | 9                                                  |
| 440V                                                      | $I_e$          | A   | 9                                                  |
| 500 V                                                     | $I_e$          | A   | 6.4                                                |
| 660 V 690 V                                               | $I_e$          | A   | 4.8                                                |
| Motor rating                                              | P              | kWh |                                                    |
| 220 V 230 V                                               | P              | kW  | 2.2                                                |
| 240V                                                      | P              | kW  | 2.5                                                |
| 380 V 400 V                                               | P              | kW  | 4                                                  |
| 415 V                                                     | P              | kW  | 4.3                                                |
| 440 V                                                     | P              | kW  | 4.6                                                |
| 500 V                                                     | P              | kW  | 4                                                  |
| 660 V 690 V                                               | P              | kW  | 4                                                  |
| AC-4                                                      |                |     |                                                    |
| Rated operational current                                 |                |     |                                                    |
| Open, 3-pole: 50 – 60 Hz                                  |                |     |                                                    |
| Notes                                                     |                |     | At maximum permissible ambient air temperature.    |
| 220 V 230 V                                               | $I_e$          | A   | 6.6                                                |
| 240 V                                                     | $I_e$          | A   | 6.6                                                |
| 380 V 400 V                                               | $I_e$          | A   | 6.6                                                |
| 415 V                                                     | $I_e$          | A   | 6.6                                                |
| 440 V                                                     | $I_e$          | A   | 6.6                                                |
| 500 V                                                     | $I_e$          | A   | 5                                                  |
| 660 V 690 V                                               | $I_e$          | A   | 3.4                                                |
| Motor rating                                              | P              | kWh |                                                    |
| 220 V 230 V                                               | P              | kW  | 1.5                                                |
| 240 V                                                     | P              | kW  | 1.8                                                |
| 380 V 400 V                                               | P              | kW  | 3                                                  |
| 415 V                                                     | P              | kW  | 3.1                                                |
| 440 V                                                     | P              | kW  | 3.3                                                |
| 500 V                                                     | P              | kW  | 3                                                  |
| 660 V 690 V                                               | P              | kW  | 3                                                  |
| DC                                                        |                |     |                                                    |
| Rated operational current open                            |                |     |                                                    |
| DC-1                                                      |                |     |                                                    |
| 12 V                                                      | $I_e$          | A   | 20                                                 |

|       |                |   |    |
|-------|----------------|---|----|
| 24 V  | I <sub>e</sub> | A | 20 |
| 60 V  | I <sub>e</sub> | A | 20 |
| 110 V | I <sub>e</sub> | A | 20 |
| 220 V | I <sub>e</sub> | A | 20 |

## Magnet systems

|                                                   |         |                  |            |
|---------------------------------------------------|---------|------------------|------------|
| Voltage tolerance                                 |         |                  |            |
| AC operated                                       |         |                  |            |
| Dual-frequency coil 50/60 Hz                      | Pick-up | x U <sub>c</sub> | 0.85 - 1.1 |
| Power consumption                                 |         |                  |            |
| AC operation                                      |         |                  |            |
| Dual-frequency coil 50/60 Hz at 50 Hz             | Pick-up | VA               | 30         |
| Dual-frequency coil 50/60 Hz at 50 Hz             | Pick-up | W                | 26         |
| Dual-frequency coil 50/60 Hz at 50 Hz             | Sealing | VA               | 5.4        |
| Dual-frequency coil 50/60 Hz at 50 Hz             | Sealing | W                | 1.8        |
| Dual-frequency coil 50/60 Hz at 60 Hz             | Pick-up | VA               | 29         |
| Dual-frequency coil 50/60 Hz at 60 Hz             | Pick-up | W                | 24         |
| Dual-frequency coil 50/60 Hz at 60 Hz             | Sealing | VA               | 3.9        |
| Dual-frequency coil 50/60 Hz at 60 Hz             | Sealing | W                | 1.8        |
| Duty factor                                       |         | % DF             | 100        |
| Switching times at 100 % U <sub>c</sub>           |         |                  |            |
| Make contact                                      |         | ms               |            |
| Closing delay                                     |         | ms               |            |
| Closing delay min.                                |         | ms               | 14         |
| Closing delay max.                                |         | ms               | 21         |
| Opening delay                                     |         | ms               |            |
| Opening delay min.                                |         | ms               | 8          |
| Opening delay max.                                |         | ms               | 18         |
| Closing delay with top mounting auxiliary contact |         | ms               | 45         |
| Reversing contactors                              |         |                  |            |
| Changeover time at 110 % U <sub>c</sub>           |         |                  |            |
| Changeover time min.                              |         | ms               | 16         |
| Changeover time max.                              |         | ms               | 21         |
| Arcing time at 690 V AC                           |         | ms               | 12         |

## Current heat losses (3- or 4-pole)

|                            |  |    |      |
|----------------------------|--|----|------|
| at I <sub>th</sub> , 50 °C |  | W  | 7.9  |
| Impedance per pole         |  | mΩ | 9.18 |

## Auxiliary contacts

|                                                                                            |                  |      |       |
|--------------------------------------------------------------------------------------------|------------------|------|-------|
| Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module |                  |      | Yes   |
| Rated impulse withstand voltage                                                            | U <sub>imp</sub> | V AC | 6000  |
| Overvoltage category/pollution degree                                                      |                  |      | III/3 |
| Rated insulation voltage                                                                   | U <sub>i</sub>   | V AC | 690   |
| Rated operational voltage                                                                  | U <sub>e</sub>   | V AC | 600   |
| Safe isolation to EN 61140                                                                 |                  |      |       |
| between coil and auxiliary contacts                                                        |                  | V AC | 300   |
| between the auxiliary contacts                                                             |                  | V AC | 300   |
| Rated operational current                                                                  |                  |      |       |
| AC-15                                                                                      |                  |      |       |
| 220 V 240 V                                                                                | I <sub>e</sub>   | A    | 6     |
| 380 V 415 V                                                                                | I <sub>e</sub>   | A    | 3     |
| 500 V                                                                                      | I <sub>e</sub>   | A    | 1.5   |
| DC L/R ≤ 15 ms                                                                             |                  |      |       |
| Contacts in series:                                                                        |                  | A    |       |
| 1                                                                                          | 24 V             | A    | 2.5   |
| 2                                                                                          | 60 V             | A    | 2.5   |

|                                                             |                 |                   |                                                                                                                                                  |
|-------------------------------------------------------------|-----------------|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| 3                                                           | 100 V           | A                 | 1.5                                                                                                                                              |
| 3                                                           | 220 V           | A                 | 0.5                                                                                                                                              |
| Conv. thermal current                                       | I <sub>th</sub> | A                 | 10                                                                                                                                               |
| Control circuit reliability                                 | Failure rate    | λ                 | <10 <sup>-8</sup> , < one failure at 100 million operations<br>(at U <sub>e</sub> = 24 V DC, U <sub>min</sub> = 17 V, I <sub>min</sub> = 5.4 mA) |
| Component lifespan at U <sub>e</sub> = 240 V                |                 |                   |                                                                                                                                                  |
| AC-15                                                       | Operations      | x 10 <sup>6</sup> | 0.2                                                                                                                                              |
| DC current                                                  |                 |                   |                                                                                                                                                  |
| L/R = 50 ms: 2 contacts in series at I <sub>e</sub> = 0.5 A | Operations      | x 10 <sup>6</sup> | 0.15                                                                                                                                             |
| Notes                                                       |                 |                   | Switch-on and switch-off conditions based on DC-13, time constant as specified                                                                   |
| Short-circuit rating without welding                        |                 |                   |                                                                                                                                                  |
| Maximum overcurrent protective device                       |                 |                   |                                                                                                                                                  |
| Short-circuit protection only                               |                 |                   | PKZM0-4                                                                                                                                          |
| Short-circuit protection maximum fuse                       |                 |                   |                                                                                                                                                  |
| 500 V                                                       |                 | A gG/gL           | 6                                                                                                                                                |
| 500 V                                                       |                 | A fast            | 10                                                                                                                                               |
| Current heat loss at a load of I <sub>th</sub> per contact  |                 | W                 | 1.1                                                                                                                                              |

### Rating data for approved types

|                              |  |      |     |
|------------------------------|--|------|-----|
| Switching capacity           |  |      |     |
| Maximum motor rating         |  |      |     |
| Three-phase                  |  |      |     |
| 200 V<br>208 V               |  | HP   | 2   |
| 230 V<br>240 V               |  | HP   | 3   |
| 460 V<br>480 V               |  | HP   | 5   |
| 575 V<br>600 V               |  | HP   | 5   |
| Single-phase                 |  |      |     |
| 115 V<br>120 V               |  | HP   | 0.5 |
| 230 V<br>240 V               |  | HP   | 1.5 |
| General use                  |  | A    | 15  |
| Short Circuit Current Rating |  | SCCR |     |
| Basic Rating                 |  |      |     |
| SCCR                         |  | kA   | 5   |
| max. Fuse                    |  | A    | 45  |

### Design verification as per IEC/EN 61439

|                                                                                                                        |                   |    |                                            |
|------------------------------------------------------------------------------------------------------------------------|-------------------|----|--------------------------------------------|
| Technical data for design verification                                                                                 |                   |    |                                            |
| Rated operational current for specified heat dissipation                                                               | I <sub>n</sub>    | A  | 22                                         |
| Heat dissipation per pole, current-dependent                                                                           | P <sub>vid</sub>  | W  | 2.39                                       |
| Equipment heat dissipation, current-dependent                                                                          | P <sub>vid</sub>  | W  | 9.56                                       |
| Static heat dissipation, non-current-dependent                                                                         | P <sub>vs</sub>   | W  | 1.8                                        |
| Heat dissipation capacity                                                                                              | P <sub>diss</sub> | W  | 0                                          |
| Operating ambient temperature min.                                                                                     |                   | °C | -25                                        |
| Operating ambient temperature max.                                                                                     |                   | °C | 50                                         |
| IEC/EN 61439 design verification                                                                                       |                   |    |                                            |
| 10.2 Strength of materials and parts                                                                                   |                   |    |                                            |
| 10.2.2 Corrosion resistance                                                                                            |                   |    | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures                                                               |                   |    | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat                                             |                   |    | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                                                       |                   |    | Meets the product standard's requirements. |


|                                                          |  |                                                                                                                                  |
|----------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------------------------|
| 10.2.5 Lifting                                           |  | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.6 Mechanical impact                                 |  | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.7 Inscriptions                                      |  | Meets the product standard's requirements.                                                                                       |
| 10.3 Degree of protection of ASSEMBLIES                  |  | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.4 Clearances and creepage distances                   |  | Meets the product standard's requirements.                                                                                       |
| 10.5 Protection against electric shock                   |  | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.6 Incorporation of switching devices and components   |  | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.7 Internal electrical circuits and connections        |  | Is the panel builder's responsibility.                                                                                           |
| 10.8 Connections for external conductors                 |  | Is the panel builder's responsibility.                                                                                           |
| 10.9 Insulation properties                               |  |                                                                                                                                  |
| 10.9.2 Power-frequency electric strength                 |  | Is the panel builder's responsibility.                                                                                           |
| 10.9.3 Impulse withstand voltage                         |  | Is the panel builder's responsibility.                                                                                           |
| 10.9.4 Testing of enclosures made of insulating material |  | Is the panel builder's responsibility.                                                                                           |
| 10.10 Temperature rise                                   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                               |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                      |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 7.0


|                                                                                                                                                                                       |    |                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|------------------|
| Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)                                                                                               |    |                  |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecI@ss10.0.1-27-37-10-03 [AAB718015]) |    |                  |
| Rated control supply voltage Us at AC 50HZ                                                                                                                                            | V  | 230 - 230        |
| Rated control supply voltage Us at AC 60HZ                                                                                                                                            | V  | 230 - 230        |
| Rated control supply voltage Us at DC                                                                                                                                                 | V  | 0 - 0            |
| Voltage type for actuating                                                                                                                                                            |    | AC               |
| Rated operation current Ie at AC-1, 400 V                                                                                                                                             | A  | 22               |
| Rated operation current Ie at AC-3, 400 V                                                                                                                                             | A  | 9                |
| Rated operation power at AC-3, 400 V                                                                                                                                                  | kW | 4                |
| Rated operation current Ie at AC-4, 400 V                                                                                                                                             | A  | 6.6              |
| Rated operation power at AC-4, 400 V                                                                                                                                                  | kW | 3                |
| Rated operation power NEMA                                                                                                                                                            | kW | 3.7              |
| Modular version                                                                                                                                                                       |    | No               |
| Number of auxiliary contacts as normally open contact                                                                                                                                 |    | 0                |
| Number of auxiliary contacts as normally closed contact                                                                                                                               |    | 0                |
| Type of electrical connection of main circuit                                                                                                                                         |    | Screw connection |
| Number of normally closed contacts as main contact                                                                                                                                    |    | 0                |
| Number of main contacts as normally open contact                                                                                                                                      |    | 4                |

## Approvals

|                                      |  |                                                           |
|--------------------------------------|--|-----------------------------------------------------------|
| Product Standards                    |  | IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking |
| UL File No.                          |  | E29096                                                    |
| UL Category Control No.              |  | NLDX                                                      |
| CSA File No.                         |  | 012528                                                    |
| CSA Class No.                        |  | 3211-04                                                   |
| North America Certification          |  | UL listed, CSA certified                                  |
| Specially designed for North America |  | No                                                        |




- 1: Overload relay
  - 2: Suppressor
  - 3: Auxiliary contact modules
- Enclosure totally insulated




Squirrel-cage motor  
 Operating characteristics  
 Starting: from rest  
 Stopping: after attaining full running speed  
 Electrical characteristics  
 Make: up to 6 x rated motor current  
 Break: up to 1 x rated motor current  
 Utilization category  
 100 % AC-3  
 Typical applications  
 Compressors  
 Lifts  
 Mixers  
 Pumps  
 Escalators  
 Agitators  
 Fans  
 Conveyor belts  
 Centrifuges  
 Hinged flaps  
 Bucket-elevators  
 Air conditioning system  
 General drives in manufacturing and processing machines

Extreme switching duty  
 Squirrel-cage motor  
 Operating characteristics  
 Inching, plugging, reversing  
 Electrical characteristics  
 Make: up to 6 x rated motor current  
 Break: up to 6 x rated motor current  
 Utilization category  
 100 % AC-4  
 Typical applications  
 Printing presses  
 Wire-drawing machines  
 Centrifuges  
 Special drives for manufacturing and processing machines







Switching duty for non-motor loads, 3-pole, 4-pole  
 Operating characteristics  
 Non-inductive or slightly inductive loads  
 Electrical characteristics  
 Make: 1 x rated current  
 Break: 1 x rated current  
 Utilization category  
 100 % AC-1  
 Typical applications  
 Electric heat





Short-time loading, 3-pole  
Time interval between two loading cycles: 15 minutes

## Dimensions








2DILE-... + MVDILE + ...DILE  
2DILE-...-G + MVDILE + ...DILE



2DILE-... + MVDILE + ...DILE  
2DILE-...-G + MVDILE + ...DILE



2DILE-... + MVDILE  
2DILE-...-G + MVDILE



## Additional product information (links)

### IL03407009Z (AWA2100-0882) Mini contactor relay

IL03407009Z (AWA2100-0882) Mini contactor relay

[https://es-assets.eaton.com/DOCUMENTATION/AWA\\_INSTRUCTIONS/IL03407009Z2020\\_05.pdf](https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03407009Z2020_05.pdf)