



Gasket set, IP65_x

Part no. SL-IP65
Catalog No. 215277
Alternate Catalog No. SL-IP65

Delivery program

Product range			SL signal towers
Single unit/Complete unit			Stand-alone device
			For increasing the degree of protection to IP65 (not for the acoustic indicator) for 3 modules $\triangleq$ 4 units
Connection to SmartWire-DT			no

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

Technical data ETIM 5.0

Low-voltage industrial components (EG000017) / Accessories for control circuit devices (EC002024)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Low-voltage switch technology (accessories) / Control circuit devices (accessories) (ec1@ss8-27-37-92-16 [ACO043007])			
Type of electrical accessory			-
Type of mechanical accessory			-

Approvals

Product Standards			IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.			E29184
UL Category Control No.			NKCR
CSA File No.			012528
CSA Class No.			3211-03
North America Certification			UL listed, CSA certified
Degree of Protection			UL/CSA Type 4X